DONGGUAN COWINT NEW MATERIAL TECHNOLOGY CO.,LTD
No.2,West Industrial Road of Jiaoli,Zhongtang Town,Dongguan
Tel: +86-769-88882603 Web:www.cowint.com
E-mail: info@cowint.com

Technical data sheet
CTS-A606S Printing Ink

Characteristics：

1, this product is environmentally friendly.
2, soft handle, not sticky hands;
3. Strong covering power, high gloss and smooth surface.
4, do not plug nets, easy to operate;
5, washable, good fastness;
6. It is suitable for printing cotton, hemp, silk, polyester, eye, and blended fabrics with easy sublimation cloth.

Environmental protection:

The SGS test results of formaldehyde, APEO, PVC/ Phthalates, Heavy metals, the four items meet the EU requirements.

The process：

Printing the basic of rubber clear →Printing the CTS-A311(1-2times) →Printing clear again →Printing rubber white or color → Finish .

Curing Process:

Temperature:130℃ with 90s.
Mesh No. : 43-48T

Advice :

1, the amount of color shall not exceed the normal standard;
2, the test should ensure that the printing is completely dry, otherwise it will affect the test results;
3, if not after heat treatment, to achieve the best effect of this product, recommended CT27 or CT31 (relatively soft) and other additives, to accelerate the cross-linking rate; or add Japan fixing agent is also available.

In verbal or written just the technical advice to show our Companies sincerity, but for our product ,the user companies still have your responsibility for test, to verify whether is suitable for the process and to use; Given the use of the products of our company process conditions are not my company control, and therefore should be fully responsible by the users themselves.