DONGGUAN COWINT NEW MATERIAL TECHNOLOGY CO.,LTD
No.2,West Industrial Road of Jiaoli,Zhongtang Town,Dongguan
Tel: +86-769-88882603 Web:www.cowint.com
E-mail: info@cowint.com

Technical data sheet
CTS-SG87MD Silicone in Primary Forms

Suitable for all kinds of needle, woven cotton, T/C cloth, cotton, Lycra cotton and modal, high elastic fabric printing.

Characteristics ：

High fastness, high elasticity, very soft, not back stick, good coverage, pressure can be folded in half a long time, it is not easy to take a bad.

Environmental protection:

The SGS test results of formaldehyde, APEO, PVC/ phthalates, heavy metals, the four items meet the EU requirements.

1.Silicone product

CTS-SG87MD：86%
Fixer：10%
Color Paste：4%
(Full agitation)
Mesh No. : 43-48T

2.The printing process

①.Fill up the ready silicone paste in the dyes directly,
②.Heat press with temperature is 160℃-180℃ with 45-60s.

3.Remarks:

It should be confirm when you add the fixer;
The testing should be ensure that the printing is completely dry, otherwise it will affect the test results;

In verbal or written just the technical advice to show our Companies sincerity, but for our product ,the user companies still have your responsibility for test, to verify whether is suitable for the process and to use; Given the use of the products of our company process conditions are not my company control, and therefore should be fully responsible by the users themselves.